

Hose Type 3/4, 4/4, 6/4, 8/4



Applications

- Waterblast:** Heat exchanger tube cleaning
- Hydraulics:** Pressure test equipment (valves, tooling and control panels), hydraulic tools (instrumentation packages for gauges, control of service equipment, hydraulic jacks, hydraulic tools)



Technical Information

- Inner Core:** Polyoxymethylene (POM)
- Pressure Support:** 4 layers of high-tensile steel wire
- Outer Cover:** Polyamide (PA)
- Colour:** Gray
- Temperature:** -30°C to +60°C [-22°F to 140°F]

Type	Ø ID	Ø OD	Working	Burst	Bend	Weight	Insert ID
3/4	3.4 mm	8.0 mm	2,000 bar	5,000 bar	110 mm	0.135 kg/m	2.0 mm
3/4	0.13 inch	0.31 inch	29,000 psi	72,500 psi	4.33 inch	0.091 lbs/ft	0.08 inch
4/4	4.0 mm	10.3 mm	2,160 bar	5,400 bar	130 mm	0.234 kg/m	1.8 mm
4/4	0.16 inch	0.41 inch	31,320 psi	78,300 psi	5.12 inch	0.157 lbs/ft	0.07 inch
6/4	6.3 mm	12.6 mm	1,500 bar	3,800 bar	180 mm	0.295 kg/m	3.5 mm
6/4	0.25 inch	0.50 inch	21,750 psi	55,100 psi	7.09 inch	0.198 lbs/ft	.14 inch
8/4	8.0 mm	14.6 mm	1,500 bar	3,800 bar	200 mm	0.390 kg/m	4.5 mm
8/4	0.31 inch	0.57 inch	21,750 psi	55,100 psi	7.87 inch	0.262 lbs/ft	0.18 inch