



Code: SF-50
P.V.C. 150 PSI RANGE (OPEN END)
BRICK RED DISCHARGE HOSE

U.S.A.

NOMINAL SIZE	I.D.	APPROX. WALL	MAX. W.P. at 70° psi	DESIGN B.P. psi	APPROX. Wt. 300ft
1-1/2"	1.61"	0.079"	150	450	80 lbs
2"	2.09"	0.087"	150	450	103 lbs
2-1/2"	2.56"	0.091"	150	450	
3"	3.07"	0.095"	150	450	164 lbs
4"	4.13"	0.102"	150	450	254 lbs
6"	6.18"	0.119"	150	450	400 lbs
8"	8.19"	0.134"	115	350	

- STND. LENGTH: 300 ft. per bale (Special order for longer lengths)
- TEMP. RANGE: -5° F to 170° F. When Temperature is -15°C and Colder, please DO NOT Handle or Transport Hoses.
- APPLICATIONS: Mines, Construction, etc.
- CONSTRUCTION: 3-Ply Polyester Yarns. Both tube and cover are extruded simultaneously to obtain maximum bonding.
- FLAME RESISTANT: **USMSHA IC-150/1** (Size 1-1/2", 2", 2/1/2")
Special order only
- CAUTION: For liability purposes, if temperature exceeds 110° F the working pressure will go down.